



EN 14785
 BlmSchV Stufe 2
 Regensburger BStV / Aachener BStV / Munchener BStV
 ART.15a B-VG / Klimafonds / LRV
 4 stelle DM.186 / Conto Termico 2.0



(Max) nominal heat output	13.9 kW
Minimum heat output	3.7 kW
Efficiency at Max	90.2 %
Efficiency at Min	92.3 %
Energy Efficiency Class (A++ / G scale)	A+
Energy Efficiency Index (EEI)	120 %
Seasonal space heating energy efficiency (η_s)	79 %
Temperature of exhaust smoke at Max	208 °C
Temperature of exhaust smoke at Min	124 °C
Particulate/OGC / Nox (13%O2)	13 - 2 - 124 mg/Nm3
CO at 13% O2 at Min and at Max	0.03 - 0.009 %
CO2 at Min and at Max	8.2 - 14.3 %
Recommended draught at Max power	10 Pa
Minimum draught allowed for minimum power	5 Pa
Mass of smoke at Min and at Max	3.3 - 7 g/sec
Hopper capacity	46 l
Type of pellet fuel	Ø 6mm L 3 ÷ 40mm
Pellet hourly consumption	0.8 - 3.1 kg/h *
Autonomy	38 - 10 h *
Heatable volume m3	253 - 397 - 695 **
Combustion air inlet	Ø 50 mm
Smoke outlet	Ø 80 mm
Nominal electrical power (EN 60335-1).	130 W (max 380 W)
Supply voltage and frequency	230 Volt / 50 Hz
Net weight	183 kg
Distance from combustible material (back/side/under)	120 mm / 250 mm / 0 mm
Distance from combustible material (front/ceiling)	800 mm / 1000 mm

* Data that may vary depending on the type of pellets used.

**Heatable volume based on the requested power per m3 (respectively 55-35-20 W/m3)