



EN 14785  
 BlmSchV Stufe 2  
 Regensburger BStV / Aachener BStV / Munchener BStV  
 ART.15a B-VG / LRV  
 4 stelle DM.186 / Conto Termico 2.0

flamme  
 VERTE



<b>(Max) nominal heat output</b>	<b>7 kW</b>
<b>Minimum heat output</b>	<b>2.7 kW</b>
<b>Efficiency at Max</b>	<b>89.6 %</b>
<b>Efficiency at Min</b>	<b>93.1 %</b>
<b>Energy Efficiency Class (A++ / G scale)</b>	<b>A+</b>
<b>Energy Efficiency Index (EEI)</b>	<b>126 %</b>
<b>Seasonal space heating energy efficiency (ηs)</b>	<b>85 %</b>
<b>Temperature of exhaust smoke at Max</b>	<b>184 °C</b>
<b>Temperature of exhaust smoke at Min</b>	<b>89 °C</b>
<b>Particulate/OGC / Nox (nominal at 13%O2)</b>	<b>14 - 4 - 116 mg/Nm3</b>
<b>CO at 13% O<sub>2</sub> at Min and at Max</b>	<b>0.015 - 0.01 %</b>
<b>CO<sub>2</sub> at Min and at Max</b>	<b>7 - 12.2 %</b>
<b>Recommended draught at Max power</b>	<b>10 Pa</b>
<b>Minimum draught allowed for minimum power</b>	<b>5 Pa</b>
<b>Mass of smoke at Min and at Max</b>	<b>3 - 4.9 g/sec</b>
<b>Hopper capacity</b>	<b>18.5 l</b>
<b>Fuel dimensions</b>	<b>Ø 6mm L 3 ÷ 40mm</b>
<b>Hourly consumption at Min and at Max</b>	<b>0.61 - 1.7 kg/h *</b>
<b>Autonomy at Min and at Max</b>	<b>20 - 7 h *</b>
<b>Heatable volume m3</b>	<b>127 - 200 - 350 **</b>
<b>Combustion air inlet</b>	<b>Ø 60 mm</b>
<b>Air inlet</b>	<b>80 cm2</b>
<b>Smoke outlet</b>	<b>Ø 80/130 mm</b>
<b>Nominal electrical power (EN 60335-1).</b>	<b>72 W (max 345 W)</b>
<b>Supply voltage and frequency</b>	<b>230 Volt / 50 Hz</b>
<b>Net weight</b>	<b>75 kg</b>
<b>Distance from combustible material (back/side/under)</b>	<b>40 mm / 300 mm / 0 mm</b>
<b>Distance from combustible material (front/ceiling)</b>	<b>800 mm / 1000 mm</b>

\* Data that may vary depending on the type of pellets used.

\*\*Heatable volume based on the requested power per m3 (respectively 55-35-20 W/m3)