

pHmeters

pH 8 Pro

Code: 50101212



TECHNICAL DATA SHEET

Performance

Temperature accuracy	±0,2 °C
Temperature compensation	0,0 ... +100,0 °C
Measuring range mV	-2000 ... +2000 mV
pH measuring range	-2,000 ... +16,000 pH
Temperature measuring range	-20,0 ... +120,0 °C
pH resolution	0,1 / 0,01 / 0,001 pH
Temperature Resolution	0,1 °C
Working temperature	0 ... +45 °C

Features

PC Communication	USB type B
Printer connection	RS 232
Criteria for stability of the measure	Med - High - Tit
Display	4.3" high-definition, backlit colour TFT
AQA	Yes
IP rating	54 IP
Display	Yes with icon
Inputs	BNC - RCA
Selectable languages	Eng - Ita - Deu - Esp - Fra - Por
Memory / Datalogger	1000
Password	Yes, 8 numeric characters
PH calibration points	1 ... 5 automatic values - 2 user values
Calibration Report	Yes, printable
pH alarm range	Min - Max
Recognised pH buffers	USA - NIST - DIN 19266
Analog view	Yes

Via della Meccanica, 25, 41012 Carpi (MO) - Italy

+39 059 653274 - info@giorgiobormac.com

Display

Si

Feeds

Power supply

100 - 240 V V

Dimensions and weight

Dimensions (WxDxH)

162 x 185 x 56 mm

Weight

0,709 Kg kg
