

XS REViO portable Multiparameter - Electrode 201 T - Cell 2301 T

Code: 50110992



TECHNICAL DATA SHEET

Standards applied

Regulations

CE

Performance

Accuracy COND	± 1% f.s.
Accuracy (pH)	± 0,002 pH
Temperature accuracy	± 0,2 °C °C
Coefficiente di temperatura	0,00 ... 10,00 % / °C % / °C
Temperature compensation	0,0...100,0 % / °C °C
TDS factor	0.40 ... 1.00
Measuring range COND	0,01 µS 1000 mS
mV ORP measuring range	-2000 ... +2000 mV
pH measuring range	-2,00 ... +20,00 pH
Salinity measuring range	0,01 ppt ... 100 ppt
TDS measuring range	0.1 mg/l ... 500 g/l
temperature measurement range	-30 ... +130,0 °C °C
COND Resolution	0,01 / 0,1 / 1 µS/cm (scala automatica) µS/cm µS/cm - mS/cm
ORP resolution	0,1 / 1 mV
pH resolution	0,1 / 0,01 / 0,001 pH
Temperature Resolution	0,1 °C °C
Reference temperature	+15 ... +30 °C °C

Features

AQA calibration	Yes
DHS compatibility	Yes
Automatic brightness control	Yes
Display	0,1 / 1 / 10
Criteria for stability of the measure	Low - Med - High (pH)
Display	High-definition, backlit colour TFT