

Tester

PC 6

Code: 50014293



TECHNICAL DATA SHEET

Standards applied

Regulations

CE

Performance

Accuracy COND	±2 % f. s.
Accuracy (pH)	±0,01 pH
Temperature accuracy	±0,5 °C °C
Coefficiente di temperatura	0.00 ... 4.00 % / °C % / °C
Temperature compensation	Yes % / °C °C
TDS factor	0.40 ... 1.00
Measuring range COND	0,01 µS ... 199,9 mS
mV ORP measuring range	-1000 ... +1000 mV
pH measuring range	-2,00 ... 16,00 pH
Salinity measuring range	0,01 mg/l ... 100,0 g/l
TDS measuring range	0,01 ppm ... 199,9 ppt
Temperature measuring range	0,0 ... +60,0 °C °C
COND Resolution	Scala automatica µS/cm µS/cm - mS/cm
ORP resolution	0.1 / 1 (automatic scale) mV
pH resolution	0.01 pH
Temperature Resolution	0.1 °C °C
Reference temperature	20,0 ... 25,0 °C °C

Features

Display	3-colour backlit LCD
IP rating	67 IP
Calibration points Cond	1 ... 3
ORP calibration points	1 user-defined
PH calibration points	1 ... 3
Swabs recognised Cond	84 µS / 1413 µS / 12,88 mS

Via della Meccanica, 25, 41012 Carpi (MO) - Italy

+39 059 653274 - info@giorgiobormac.com

Recognised pH buffers

5 US pads

Feeds

Power supply

2 x AAA batteries 1.5 V V

Dimensions and weight

Dimensions (WxDxH)

40 x 200 mm mm

Weight

0.11 Kg kg
