



EN 14785
BlmSchV Stufe 2
Regensburger BStV / Aachener BStV / Munchener BStV
ART.15a B-VG / LRV
4 stelle DM.186 / Conto Termico 2.0



(Max) nominal heat output	13.8 kW
Minimum heat output	3.4 kW
Efficiency at Max	90.5 %
Efficiency at Min	93.2 %
Energy Efficiency Class (A++ / G scale)	A+
Energy Efficiency Index (EEI)	120 %
Seasonal space heating energy efficiency (η_s)	79 %
Temperature of exhaust smoke at Max	205 °C
Temperature of exhaust smoke at Min	106 °C
Particulate/OGC / Nox (13%O2)	13 - 1 - 150 mg/Nm3
CO at 13% O2 at Min and at Max	0.034 - 0.009 %
CO2 at Min and at Max	8.1 - 14.2 %
Recommended draught at Max power	10 Pa
Minimum draught allowed for minimum power	5 Pa
Mass of smoke at Min and at Max	3.1 - 7.1 g/sec
Hopper capacity	46 l
Type of pellet fuel	Ø 6mm L 3 ÷ 40mm
Pellet hourly consumption	0.8 - 3.1 kg/h *
Autonomy	38 - 10 h *
Heatable volume m3	251 - 394 - 690 **
Combustion air inlet	Ø 50 mm
Smoke outlet	Ø 80 mm
Nominal electrical power (EN 60335-1).	130 W (max 380 W)
Supply voltage and frequency	230 Volt / 50 Hz
Net weight	183 kg
Distance from combustible material (back/side/under)	120 mm / 250 mm / 0 mm
Distance from combustible material (front/ceiling)	800 mm / 1000 mm

* Data that may vary depending on the type of pellets used.

**Heatable volume based on the requested power per m3 (respectively 55-35-20 W/m3)