

# Multiparameters

## PC 60 VioLab

Code: 50103942



### TECHNICAL DATA SHEET

#### Standards applied

Regulations	CE
<b>Performance</b>	
Accuracy COND	±2 % f.s.
Accuracy (pH)	±0,02 pH
Temperature accuracy	±0,5 °C °C
Coefficiente di temperatura	0,00 ... 10,00 % / °C % / °C
Temperature compensation	0,0 ... +100,0 % / °C °C
TDS factor	0.40 ... 1.00
Measuring range COND	0,00 µS ... 200 mS
mV ORP measuring range	-1000 ... +1900 mV
pH measuring range	-2,00 ... +16,00 pH
Salinity measuring range	0,1 ppm ... 100 ppt
TDS measuring range	0.1 mg/l ... 200 g/l
Temperature measuring range	-10,0 ... +110,0 °C °C
COND Resolution	0,01 / 0,1 / 1 µS/cm (scala automatica) µS/cm µS/cm - mS/cm
ORP resolution	0,1 / 1 mV
pH resolution	0,1 / 0,01 pH
Temperature Resolution	0,1 °C °C
Working temperature	0 ... +45 °C °C
Reference temperature	+15 ... +30 °C °C
<b>Features</b>	
DHS compatibility	Yes
Printer connection	RS 232
Display	0,1 / 1 / 10
Criteria for stability of the measure	Low - Med - High (pH)
Display	High-definition, backlit colour LCD

---

Via della Meccanica, 25, 41012 Carpi (MO) - Italy

+39 059 653274 - info@giorgiobormac.com

IP rating	54 IP
Inputs	BNC - RCA - banana 4 mm
Memory	1000 data
Calibration points Cond	1...4
ORP calibration points	1
PH calibration points	1...3 automatic values - 2 user values
Calibration Report	Yes, printable
Swabs recognised Cond	84 $\mu$ S - 147 $\mu$ S - 1413 $\mu$ S - 12,88 mS - 111,8 mS - 1 valore user
Recognised pH buffers	USA - NIST - 2 custom values
Display	Si

## Feeds

---

## Dimensions and weight

---

Dimensions (WxDxH)	160 x 140 x 45 mm mm
Weight	0.38 Kg kg

---