

Conductivity meters

Cond 60 VioLab

Code: 50103082



TECHNICAL DATA SHEET

Standards applied

Regulations

Performance

Accuratezza COND	±2 % f.s.
Temperature accuracy	±0.5 °C °C
Temperature coefficient (max)	0,00 ... 10,00 % / °C % / °C
Temperature compensation	0,0 ... +100,0 % / °C °C
TDS factor	0.40 ... 1.00
Measuring range COND	0.00 µS ... 200 mS
Salinity measuring range	0,1 ppm ... 100 ppt
TDS measuring range	0.1 mg/l ... 200 g/l
Temperature measuring range	0.0 ... 100.0 °C °C
COND Resolution	0,01 µS/cm µS/cm - mS/cm
Temperature Resolution	0.1 °C °C
Working temperature	0 ... +45 °C °C
Reference temperature	+15 ... +30 °C °C

Features

PC Communication	Micro USB
Printer connection	RS 232
Display	High-definition, backlit colour LCD
AQA	Yes
IP rating	54 IP
Inputs	BNC - RCA
Memory	1000
Output	Micro USB - RS 232
Calibration points Cond	1 ... 4

Via della Meccanica, 25, 41012 Carpi (MO) - Italy

+39 059 653274 - info@giorgiobormac.com

Calibration Report

Yes, printable

Feeds

Power supply

100 - 240 V V

Dimensions and weight

Instrument weight

0.38 Kg kg
